



- Not available
- ✕ Basic version
- ♠ Special design

ARCUSBASIC



ARCUSDETECT M



ARCUSDETECT H



IEC 61243-1

| Nominal voltage (kV)                       | .6-24 | up to 36 | up to 420 |
|--------------------------------------------|-------|----------|-----------|
| Single voltage range tester                | ✕     | ✕        | ✕         |
| Wide voltage range tester                  | ○     | ✕        | ✕         |
| Frequency: 50 Hz                           | ✕     | ✕        | ✕         |
| Frequency: 16.7 Hz                         | ♠     | ♠        | ♠         |
| Visual indication                          | ✕     | ♠        | ♠         |
| Audible and visual indication              | ○     | ✕        | ✕         |
| Indoor use                                 | ✕     | ✕        | ♠         |
| Outdoor use                                | ✕     | ✕        | ✕         |
| Self-testing including extension electrode | ✕     | ✕        | ✕         |
| Easy battery change                        | ✕     | ✕        | ✕         |
| Threaded fork contact                      | ♠     | ♠        | ✕         |
| Threaded extension                         | ○     | ♠        | ○         |
| Carrying bag                               | ♠     | ♠        | ✕         |
| Case                                       | ♠     | ♠        | ♠         |
| Wall holder                                | ♠     | ♠        | ♠         |

LISAINFO

LISAINFO

LISAINFO